



FICHA TÉCNICA

Technical Data Sheet



Piedra en acabado mate Matte finish stone	80 X 160 CM. 32 X 64 IN.	Porcelanato esmaltado. Rectificado. Glazed porcelain tile. Rectified.	
5 Caras 5 Faces	PEI 4 Alto Tráfico High Traffic	Variación Alta High Variation	100% Pasta Blanca White body

Uso Usage

Interior Interior	Baño Bathroom	Cocina Kitchen	Exterior Exterior	Comercial Commercial
----------------------	------------------	-------------------	----------------------	-------------------------

Porcelanato mate / Matte porcelain tile

Características técnicas / Technical specifications

100%	Pasta blanca / White body		
Separación de boquilla / Grout size	2 mm		
PEI	4		
Resistencia química / Chemical resistance	Conforme	ASTM C650	
DCOF / Dynamic Coefficient of Friction	>0.42	ASTM C1028	
Absorción de agua / Water absorption	≤0.5%	ASTM C373	
MOHS	5-8	ASTM C1028	
Resistencia de flexión / Breaking strength	>350 kg	ISO 10545-4	
Shock térmico / Thermal shock resistance	Conforme	ASTM C484	
Resistencia a helada / Frost resistance	Conforme	ASTM C1026	
Resistencia a manchas / Stain resistance	Conforme	ASTM C1378	
Resistencia de abrasión / Abrasion resistance	Conforme	ANSI A137	
Información de Embalaje / Packaging Information	PZS-CAJA / PCS-BOX	M ² -CAJA / FT ² -BOX	KG-CAJA / LBS-BOX
	2	2.56 / 27.55	59.65 / 131.5

Cesantoni S.A. de C.V. certifica que los resultados anteriores fueron obtenidos en análisis de laboratorio elaborado por el departamento de Control de Calidad.

Cesantoni certifies that the above results were obtained in laboratory testing performed by the quality control department.

www.cesantoni.com.mx contacto@cesantoni.com.mx

