



Ficha Técnica Technical Specifications

SUPER GRES / SUPER GRES Tile

Formato Nominal / Nominal Size:
45 x 90 cm Rectificado / 18" x 36" Rectified

Formato Real / Real Size:
45 x 91 cm Rectificado / 18" x 36" Rectified

Link: [Pasta blanca vs. Pasta Roja](#)



	Separación de boquilla / Grout separation	2 mm / 1/12"	
	P.E.I.	4 (Tráfico: Medio - Alto)	
	Tono y Textura Mezclado / Shade and Texture Mixture	Alto / High	
	Resistencia al ataque químico / Chemical Resistance	Conforme / Compliant	A.S.T.M. C650
	Coefficiente Dinámico de Fricción / DCOF	≥ 0.42	A.S.T.M. C1028
	Absorción de agua / Water absorption	≤ 3 %	A.S.T.M. C373
	MOHS	5 - 8	A.S.T.M. C1028
	Resistencia a la flexión / Breaking Strength	≥ 250kg / 551 lbs	ISO 10545-4
	Resistencia al shock térmico / Thermal Shock Resistance	Conforme / Compliant	A.S.T.M. C484
	Resistencia a helada / Frost Resistance	Conforme / Compliant	A.S.T.M. C1026
	Resistencia a las manchas / Stain Resistance	Conforme / Compliant	A.S.T.M. C1378
	Resistencia a la abrasión / Abrasion Resistance	Conforme / Compliant	ANSI A137

	Información de Embalaje / Packaging Information	FORMATO / SIZE 45 x 90 cm 18" x 36"	PZS-CAJA / PCS-BOX 4	M ² -CAJA / FT ² -BOX 1.63 / 17.54	KG-CAJA / LBS-BOX 34.50 / 76.06
--	---	--	-------------------------	---	------------------------------------

Cesantoni S.A. de C.V. certifica que los resultados anteriores fueron obtenidos en análisis de laboratorio elaborado por el departamento de Control de Calidad.
Cesantoni certifies that the above results were obtained in laboratory testing performed by the quality control department.